

- +IP 20
- 
- LOA
- 5 YRS
- ldt

### PHYSICAL DATA

#### FEATURES

- Material: Aluminum with PMMA diffuser
- Modular structure, easy for driver replacement
- 1.5mm profile thickness
- Available in single and continuous linear, easy for connection & maintenance
- 3CCT selectable
- Magnetic uplight module

- Available in 3 lengths: 1200mm / 1500mm / 3000mm
- Direct lighting wattages: 36W / 45W / 90W
- ID/DR lighting wattages: 36W / 45W / 90W
- Aluminum end cap

#### MOUNTING

Surface or Suspended

#### APPLICATION AREAS

Indoor, Commercial, Residential, Retail

#### OPTIONS & ACCESSORIES

- Dimming: On/Off DALI
- Suspension accessories and extra 2.4m rollable diffuser


### TECHNICAL DATA

### LSL13352CCT30

|                       |                        |
|-----------------------|------------------------|
| LAMP                  | LED                    |
| TOTAL POWER (W)       | 35W                    |
| SYSTEM OUTPUT (LM)    | 4500LM                 |
| EFFICACY (LM/W)       | 130LM/W                |
| CCT (K)               | 3000K / 3500K / 4000K  |
| CRI (Ra)              | 90                     |
| BEAM ANGLE            | 110° DOWN   120° UP    |
| OPERATING VOLTAGE-VAC | 220 - 240V             |
| OPERATING TEMP °C     | -20°C To 40°C          |
| RATED LIFE (HRS)      | 50 000HRS L90B10       |
| THD                   | <20%                   |
| MAC ADAM STEP         | SDCM <3                |
| WEIGHT (KG)           | 3.5KG                  |
| DIMENSIONS            | W:60 x L:1200 x H:80mm |



#### SELECTABLE UP/DOWN DISTRIBUTION



# LIGHTS BY LINEA

EST. 1990

DESIGN & TECHNICAL CERTAINTY

E&OE MAY OCCUR