



PHYSICAL DATA

FEATURES

- Material: Roll-formed Steel and PMMA Lens
- Lense fixation without screw
- Energy saving plus, 50% lower energy consumption
- Modular design, easy installation

OPTIONS & ACCESSORIES

- Fixed CCT & 3CCT selectable
- DALI Dimmable
- Suspension kit & chain, ceiling clip, input cable, feed-in-connector, cable gland, end cap, L-norde, T-norde, X-norde

- Available in 2 lengths: 750mm / 1500mm
- Available in 3 wattages: 30W / 50W / 80W
- Available beam angles: 60° / 90° / 120°
- Sensor & Emergency version available upon request
- Module options: Track light, emergency, display, and black cover module

MOUNTING

Suspended or Surface mounted

APPLICATION AREAS

Indoor, Commercial, Schools, Retail, Residential

TECHNICAL DATA

LSL1650409030

LAMP	LED
TOTAL POWER (W)	50W
SYSTEM OUTPUT (LM)	8000LM
EFFICACY (LM/W)	160LM/W
CCT (K)	4000K
CRI (Ra)	>80
BEAM ANGLE	90°
OPERATING VOLTAGE-VAC	220 -240V
RATED LIFE (HRS)	50 000HRS L80
POWER FACTOR	>0.9
UGR	<19
MAC ADAM STEP	SDCM <3
DIMENSIONS	W:67 x L:1500 x H:23mm



LIGHTS BY
LINEA

EST. 1990

DESIGN & TECHNICAL CERTAINTY

E&OE MAY OCCUR